

## Digital Video Recorder NV-DVR5508/DVD



### Features

- PENTAPLEX: simultaneous recording, live monitoring, playback, archiving/mirroring and networking
- Operating system based on Linux
- Real-time display
- Recording speed: up to 200 fps
- TRIPLEX function: simultaneous recording, live monitoring and playback of a chosen camera on the main monitor
- MPEG-4 compression
- Recording resolution:
  - 720 x 576
  - 720 x 288
  - 360 x 288
- 4 spot monitor outputs with matrix switcher function (16 x 4)
- Storage of max. 9 TB, 1 HDD 250 GB in-set included
- Recording resolution, speed and quality defined individually for each camera
- Advanced schedule recording & motion detection functions
- Pre- & post-alarm functions
- 4-channel real-time audio recording
- External devices support ("Text-in" feature): ATM, POS, AC etc.
- Advanced search functions of recorded images
- PTZ control directly from the device or through the network
- Possibility of controlling NOVUS® cameras equipped with RS-485 interface
- Protocol: Novus-C, Novus-C1, Pelco-D and others
- NV-KBD60 & NV-KBD30 keyboards compatible
- Built-in DVD-RW drive
- Backup: onto HDD or USB Flash Memory through USB port, CD/DVD & through the network
- Networking (simultaneous connections with multiple DVRs and alarm e-mail notification)
- Software: RASplus application (for remote administration, live monitoring and recorded data search) with a built-in module for graphical object visualization (maps)
- Self-diagnostic functions with automatic notification
- User friendly multi-lingual OSD
- Covert camera function
- Power supply: 100~240 VAC

Specifications	Description
Operation Mode	PENTAPLEX
Operating System	Linux
Video Input	8 x BNC, loop-through
Video Output	1 Main Monitor output (BNC, Y/C and/or VGA), 4 Spot Monitor output (BNC)
Alarm Input	8
Alarm Output	7 OC, 1 relay outputs
Audio Input	4 x RCA

Specifications	Description
Audio Output	1 x RCA
Recording Speed	Up to 100 fps for 720 (H) x 288 (V), 200 fps for 360 (H) x 288 (V)
Compression	MPEG-4 - own algorithm (4 quality levels)
Recording Resolution	720 (H) x 576 (v), 720 (H) x 288 (V) and 360 (H) x 288 (V) - defined individually for each channel
Recording Mode	Time-lapse, Event (Alarm, Motion detection and/or "Text-in")
Display Speed	200 fps („real-time")
Display Screen	Full screen, 4, 9, PiP, sequence, user defined, freeze image function, digital zoom of a chosen screen area: x2, x3, x4
Motion Detection	256 detection windows (16x16 grid) with sensitivity, active areas size & cells number needed for alarm activation defined individually for each channel, additional disappeared object detection function
Video Loss Detection	Yes
Schedule Recording	Individually adjustable for each day/specific days (holidays etc.) per camera, combination of individual recording modes possibility
Recorded Data Search	By date/time or events (motion, disappeared object, "Text-in")
Event History Log	Up to 10 000 alarm events
Time Synchronization	Automatic time synchronization with NTP server
System Diagnostic	Automatic control of HDD bad sectors number ("Health") & temperature status with local and network notification function
Storage	Max. 9 TB - supports up to 3 internal HDDs (max. 1 TB each) and external HDDs through SCSI port, 1 HDD 250 GB in-set included
Backup	Onto CD/DVD, HDD or USB Flash Memory through USB port, through the network
Archiving	Automatic archiving onto internal & external HDDs connected through USB or SCSI ports
Mirroring	Automatic archiving onto internal or external HDD connected through SCSI or USB port
DVD-RW Drive	Built-in
External Ports	1 x Ethernet - RJ-45 interface, 3 x USB 2.0 for external drives (HDD, PC mouse, Flash Memory, POS, ATM, AC etc.) 1 x SCSI for external HDDs, 1 x RS-485 for PTZ cameras, NV-KBD60 & NV-KBD30 keyboards, POS, ATM, AC etc. 1 x RS-232 for POS, ATM, AC etc.
PTZ Functions	PTZ cameras control directly from the device and through the network (RASplus, IE)
Protocol	Novus-C, Novus-C1, Pelco-D
Control	Front panel, IR remote control (in-set included), Network (RASplus, IE), NV-KBD60 & NV-KBD30 keyboards, USB PC mouse
Set-up	Multi-lingual On Screen Display (OSD)
Software	RASplus
User Authorization	Multi-level password protection
Auto System Recovery	Hardware WATCHDOG function
Power Supply	100~240 VAC
Power Consumption	Approx. 100 W with 4 HDDs
Operating Temperature	5°C ~ 40°C
Relative Humidity	0 % ~ 80 % (non-condensing)
Dimensions (mm)	430 (W) x 88 (H) x 403 (D)
Weight	10.2 kg (without HDD)
Rack Mount	Standard EIA 19", 2U
*	The list of recommended disk models and their capacity is available on Novus website in the compatible disks file in the products tab