

## Monitor LCD NVM-432LCD(A)



### Features

- Professional high resolution TFT LCD monitors
- Digital 3D comb filter for sharp and clear picture with natural colors
- Panel type: 32"
- 16:9 LCD panel format
- 4-channel real-time multiplexer built-in
- Multi-screen display (PC/Quad/POP screen/Full screen)
- Image storage: up to 60 still images
- Digital zoom: 2x
- Alarm input/output: 1
- Video input: 4 x BNC, S-Video, VGA, RCA
- Audio input: RCA
- Internal speakers
- Key Lock function and menu password protection
- Multi-lingual On Screen Display (OSD)
- Rugged metal design
- Power supply: 24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included)

Specifications	Description
Panel Type	32" color TFT LCD Panel
Screen Size (Diagonal)	812.8 (mm)
Viewable Size (mm)	697.685 (H) x 392.256 (V)
CRT Dot Pitch	0.51075 x 0.51075
Resolution	580 TVL
Viewing Angle (L/R/T/B)	89°/89°/89°/89°
Contrast Ratio	3000:1
Brightness	500 cd/m2
Display Color	16.7 mln
Response Time	8 ms
Video Input	4 x CVBS: BNC loop-through connector, 1 x S-Video: Mini-DIN 4 Pin connector, 1 x VGA, 1 x YPbPr: 3 x RCA
Audio Input	Stereo 1 Vp-p/1 kHz
Speaker Output	2 x 5 W
Alarm Input	1 input (NO/NC) with individual polarity selection
Alarm Output	1 output (NO/NC)
Operation	Multi-lingual On Screen Display (OSD)
Operation System	PAL/NTSC (Auto Scan)
Case	Metal
Access Security	Key Lock function, menu password protection

Specifications	Description
Power Supply	24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included)
Power Consumption	180 W
Operating Temperature	0°C ~ 40°C
Dimensions (mm)	804 (W) x 512 (H) x 96.8 (D)
Weight	18.5 kg
In-set Included	DC adapter, Power cord, VGA cable, IR remote control